



Carbon / Sulfur Analyzer CS-580A

General Information

ELTRA's CS-580A is the ideal analyzer for the simultaneous determination of carbon and sulfur in organic samples.

ELTRA's 580A analyzers (A = Autoloader) are equipped with an automatic sample loader, allowing for analysis of large numbers of samples without operator intervention. The sample loader is available in two versions to accommodate 36 or 130 crucibles. The CS-580A is based on the technology of the CS-580 analyzer and features a vertical resistance furnace with ceramic tube.

The temperature can be set in steps of 1 °C to a maximum of 1,550 °C. Thanks to sample weights of up to 500 mg and more even inhomogeneous materials can be reliably analyzed. The analyzer can be equipped with up to four independent infrared cells according to the user's requirements, allowing for a great variety of applications.



Application Examples

ashes, building materials, coal, coke, gypsum, limestone, oil, plant materials, rubber, sand, soils, soot, tobacco, waste, ...

Product Advantages

- Simultaneous carbon and sulfur determination with minimal sample preparation
- wide range of organic materials can be analyzed
- rapid, precise, accurate and reliable element determination
- resistance furnace can be set up to 1550 °C in steps of 1 °C
- customized infrared cells provide wide, dynamic measuring range
- due to gold IR path, increased cell live time for analysis of halogen or acid containing samples
- powerful software (multilingual, customized display, export of results)
- single and multipoint calibration
- low maintenance
- robust design allows usage in production control and laboratory

Features

Measured elements	carbon, sulfur
Samples	organic
Furnace alignment	vertical
Sample carrier	ceramic crucibles
Field of application	agriculture, biology, chemistry / plastics, coal / power plant, construction materials, environment / recycling, medicine / pharmaceuticals
Furnace	resistance furnace (ceramic tube),



Carbon / Sulfur Analyzer CS-580A

	adjustable up to 1550 °C (steps of 1 °C)
Detection method	solid state infrared absorption
Number of IR cells	1 - 4
Material of IR path	gold
Typical analysis time	60 - 120 s
Chemicals required	magnesium perchlorate, sodium hydroxide
Gas required	oxygen 99.5 % pure (2 - 4 bar / 30 - 60 psi) compressed air (4 - 6 bar / 60 - 90 psi)
Power requirements	230 V, 50/60 Hz, max. heat up current 2000 W
Dimensions (W x H x D)	55 x 100 x 60 cm (analyzer) 85 x 35 x 45 cm (Autoloader for 130 crucibles)
Weight	~ 90 kg (analyzer) ~ 15 kg (Autoloader for 130 crucibles)
Required equipment	balance (resolution 0.0001g), monitor, PC
Required accessories	Autoloader (for 36 or 130 crucibles)
Optional accessories	TIC module, voltage stabilizer 5 KVA

Function Principle

Operation CS-580A

In the CS-580A the samples are weighed into crucibles. Then a gripper places the samples from the Autoloader on the pedestal. The samples are loaded consecutively into the furnace for combustion. The average analysis time is 60 to 120 seconds. Detector signals and instrument parameters are displayed during analysis. Evaluation of the signals and display of the results are done automatically; the data can be transferred to a laboratory information management system (LIMS). The analyzers require minimum maintenance. The particle filters and chemicals which need to be maintained are easily accessible.

Measuring Principle CS-580A

In the CS-580A analyzers the sample is burnt in an oxygen atmosphere at temperatures of up to 1,550 °C. The furnace temperature can be freely selected in steps of 1 °C. The combustion gasses (CO₂, H₂O, SO₂) coming from the furnace pass through a dust filter. After the water vapor is chemically absorbed, the dried CO₂ and SO₂ gas is detected in the additional infrared cells. Depending on the configuration, it is possible to combine up to four infrared cells with different sensitivities.



Carbon / Sulfur Analyzer CS-580A

Order data

ELTRA CS-580A "Helios"

(Please order PC, monitor, balance, Autoloader and consumables (starter-kit, anhydron, sodium hydroxide) separately)

Measuring ranges at 500 mg sample weight

88100-4015	CS-580A 1xC 0.05 - 100% C
88100-4016	CS-580A 1xS 0.005 - 2% S
88100-4017	CS-580A 2xC 0.005 - 12% C 12 - 100% C
88100-4018	CS-580A 2xS 0.005 - 2% S 2 - 20% S
88100-4019	CS-580A 1xC 0.05 - 100% C + 1xS 0.005 - 2% S
88100-4020	CS-580A 1xC 0.05 - 100% C + 2xS 0.005 - 2% S 2 - 20% S
88100-4021	CS-580A 2xC 0.005 - 12% C 12 - 100% C + 1xS 0.005 - 2% S
88100-4022	CS-580A 2xC 0.005 - 12% C 12 - 100 % C + 2xS 0.005 - 2 % S 2 - 20% S

Further measuring range combinations on request

Autoloader

14535	Autoloader for 36 crucibles
14533	Autoloader for 130 crucibles

PC, Monitor, Balance

71015	Computer with dual core processor, 300 GB HDD, 4 GB RAM, Windows operating system, DVD-ROM, keyboard, mouse
71016	Monitor, TFT
88600-0002	Balance (resolution 0.0001 g)
71002	Printer

Accessories

38001	TIC-Module
72070	Oxygen regulator
71090	Voltage Stabilizer 5 KVA

Consumables

Required consumables

88500-0005	Starter-kit for 500 analyses (500 crucibles, 50 g glass wool, 50 g iron phosphate)
90200	Anhydron (magnesium perchlorate), 454 g



Carbon / Sulfur Analyzer CS-580A

90210

Sodium hydroxide, 500 g

Optional consumables

90149

Ceramic crucibles, premium, Ø 1", foil-wrapped,
1,000 pieces

90331

Glass wool, 454 g

88600-0008

Combsolid, 100g

92511-3020

Calibration standard - Coal, 50 g 0.5 - 1.0% S

90800

Graphite, 50 g

90810

Calcium carbonate, 100 g

92610

Tube of high vacuum grease

Spare and Wear Parts

77501

Heating elements, 1 set (4 pieces)

35540

Combustion tube 50x40x525 mm

35541

Lance

35542

Pedestal

11170

Balston-filter

09092

Reagent tube 54x36x280

35516

O-ring

70150

O-ring 6x2.5

70320

O-ring 20x5

70330

O-ring 21x2

70255

O-ring 10x1.5

70427

O-ring 49x5

70428

O-ring 49x7

36914

Thermocouple

77032

Circuit breaker 20A